

SNIPE CLASS RACING ASSOCIATION

MEASUREMENT DATA SHEET FOR CERTIFIED BOATS

Revised February 2019

This page to be used for all boats. For measurements in Italic refer to the Class Rules



HULL NUMBER	32096	BUILDER	MAS GROUP
MODEL	DB R 1	YEAR OF MANUFACTURE	2026
OWNER	ENRIQUE QUINTERO	COUNTRY	USA

BARE HULL	☐	COMPLETE	☐	INCOMPLETE	☒
HULL MATERIAL: WOOD	☐	FIBERGLASS	☐	make note of	
DECK MATERIAL: WOOD	☐	FIBERGLASS	☐	incomplete items	
FROM CERTIFIED MOULD	☐			filling the cells with NO	

HULL WEIGHT (min 125kg)	127.8	MAST LENGTH (Rules C.9.2, F.3.4)	6500
TOTAL WEIGHT (min 172.8kg)		Limiting marks & pin	✓
CORRECTOR WEIGHTS (max 15kg)		Corrector weights (max 100gr)	NO
MOI		BOOM LENGTH (max 2642mm)	2585
Spring set #		Limiting marks & pin	✓
JIB FITTING		POLE LENGTH (max 2642mm)	2640
(279-330mm hor. From Hull Datum Point) ✓		RUDDER DIMENSIONS	✓
max 45mm vert. above sheerline)		Weight (min. 2.72kg)	3.01
SHROUDS (1778-1981mm from HDP)	1778	Corrector weights (Rule C.8.5)	NO
MAST HOLE (min 1494-mm from HDP)	1494	Parallel to transom (tolerance 2mm)	✓
UPPER GUDGEON (Rule D.2.3)	410	DAGGERBOARD DIMENSIONS	✓
LOWER GUDGEON (Rule D.2.3)	156	Band	✓
GUDGEONS DIAMETER (Rule D.2.3)	8	Safety line (max 610mm long)	
		Restraining system (hooks or tablet)	

Insert the **actual** measurement in the cells marked as ☐

Mark corrector weights position and amount below. Data to be copied on the Official Snipe Label



DATE MEASURED 22/07/26 MEASURER'S STAMP

MEASURER'S NAME TOSCANI GIOVANNI

NOTES:

22/07/26

Snipe Class International Racing Association

12 SCIRA
Measurer
ITALY

SCIRA Measurement Data Sheet

To be used with the 80/20 true baseline measurement frame

For boats built from January 1st, 2018. For older boats use the MDS in force in the year of manufacturing

Owner ENRIQUE QUINTERO Date 27/02/26
 Hull 32096 Builder MAS GROUP Material FIBREGLASS

NEW MOULD: FIRST ☐ OR ☐ OF 5 CERTIFICATION RENEW ☐ Y/N

DO NOT COMPLETE IF FROM A CERTIFIED MOULD

Chine						
	Height				Width	
Station	Starboard	Port	Total	Allowable Range	Actual	Allowable Range
1				838-864		527-540
2				724-749		991-1003
3				673-699		1232-1245
4				680-705		1270-1283
5				762-787		1137-1149
Transom				902-927		952-965

Sheer						
	Height				Width	
Station	Starboard	Port	Total	Allowable Range	Actual	Allowable Range
1				1499-1549		895-921
2				1391-1441		1346-1372
3				1333-1384		1511-1537
4				1321-1372		1473-1499
5				1321-1372		1270-1295
Transom				1384-1435		1022-1048

12 SCIRA
 Measurer
 ITALY
 27/02/26

Snipe Class International Racing Association

HULL 32096

SCIRA MDS Rev. "J-d" - July 2019

Keel				
Station	Height		Width	
	Actual	Allowable Range	Actual	Allowable Range
400mm		223-235		
1		162		Min 51
2		89-101		99-105
3		51-63		99-105
4		58-70		99-105
5		114		99-105
Transom		166-178		99-105

Stem Offset		
up from baseline	back from HDP	Actual
267	267-279	
305	194-206	
337	153-165	
381	108-120	
457	54-66	
527	26-38	
311 to 387	Intersection of chine extension	

Miscellaneous					
Measurement	Actual	Allowable Range	Measurement	Actual	Allowable Range
LOA		4711-4737	Chine radius at st. 1		Max 19
Horizontal transom offset		203-229	Chine radius st. 2 to transom		Max 3
Hull Datum Point height		683-708	Deck height		Max 127
Bow radius		Max 25	Cockpit width		Max 1016

Topside Measurements					
Measurement	Actual	Allowable Range	Measurement	Actual	Allowable Range
Aft end of dagg. slot from Hull datum point		2438-2464	Heel point to sheer (vertical)	393	390-400
Top of case parallel to baseline		tolerance 2	Mast hole in the deck	170 x 60	Max 256x76
Aft edge of slot perpendicular to baseline		tolerance 2	Length of foredeck		Min 1842
Forward edge of slot perpendicular to baseline		tolerance 6	Length of aft deck		Min 457
Keel to top of daggerboard case	312	310-313	Sheer strikes		Max 32
Length of daggerboard slot	522	Max 546	Gunwale radius		Max 12
Width of daggerboard slot	12	Max 13	Splashboard		Min 51 x 610

Measurer TOSCANI GIOVANNI

27/02/26

Stamp nr. 12

SCIRA
Measurer
ITALY

Snipe Class International Racing Association